



## J60 KVA Genset



Generating set picture may include optional accessories

### Output Ratings

Generating Set Model	Prime	Standby
380-415V, 3 ph, 50 Hz, 1500rpm	60kVA	66 kVA
	48 KW	52.8 KW

### Rating Definitions

#### Prime Power - Model J60

These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply %10 overload power for 1 hour in 12 hours.

#### Standby Power - Model J60

These ratings are applicable for supplying continuous electrical power in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated.

### ALTERNATOR DATA

Make	Leroy Somer
Model	LSA42.3L9 / TAL 042H
No. of bearings	1
Insulation class	H
Total Harmonic Content	at no load <3.5% - on load <5%
Wires	6
Ingress Protection	IP23
Excitation System	SHUNT
Winding Pitch	2/3 (wdg 3)
AVR Model	R120/R220
Overspeed	2250 mn <sup>-1</sup>
Voltage Regulation (steady)	± 1%
Short Circuit Capacity	-

AREP Excitation System Available as Optional.

### ENGINE / TECHNICAL DATA

Engine Make	Perkins	
Engine Model	1103A-33TG2	
Governing Type	Mechanical	
Number of Cylinders	3	
Cylinder Arrangement	Vertical in line	
Bore and Stroke mm	105 x 127	
Displacement / Cubic Capacity litres	3.3	
Induction System	Turbocharged	
Cycle	4 stroke	
Combustion System	Direct Injection	
Compression Ratio	17.25:1	
Rotation	Anti-clockwise, viewed from flywheel	
Cooling System	Water - cooled	
Frequency and Engine Speed	50Hz & 1500rpm	
	Prime	Standby
Gross Engine Power kW (hp)	55 (73.8)	60.5 (81.1)
Fuel Consumption @ 50% load L/hr	7.2	-
@ 75% load L/hr	10.4	-
Fuel Consumption @ 50% load L/hr	13.9	15.4
Total Lubrication System Capacity litres	7.9	7.9
Total Coolant Capacity (inc. radiator) litres	10.2	10.2
Exhaust Temperature: °C	557	571
Radiator Cooling Air Flow (Min): m3/sec	1.48	1.48
Combustion Air Flow: m3/min	3.8	3.9
Exhaust Gas Flow: m3/min	10.1	10.4
Fuel Tank Capacity: litres	87	87

**Note:** Output ratings are presented at 25°C air inlet temperature, barometric pressure 100 kPa, relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 55°C), humidity (up to 99%) and higher altitudes. De-rating may apply, please consult your dealer for specific site ratings.

### Dimensions and Weights

Length cm	Width cm	Height cm	Weight* kg (wet)
165	73	132	765

# Standard Specifications

## 1. ENGINE

Perkins four stroke heavy duty high performance industrial type diesel engine.

## 2. ENGINE FILTRATION SYSTEM

- Cartridge Type dry air filter.
  - Cartridge Type fuel air filter.
  - Full flow lube oil filter.
- All filters have replaceable elements.

## 3. COOLING RADIATOR

Radiator and cooling fan, designed to cool the engine at high ambient temperature

## 4. EXHAUST SYSTEM

Heavy duty Industrial Exhaust Silencer

Silencer noise reduction level	14 (dB)
Maximum allowable back pressure	10.0 @ 50Hz 15.0 @ 60Hz

## 5. CIRCUIT BREAKER TYPE

ABB 3 pole MCCB (4 pole is optional)

## 6. ALTERNATOR

Perkins four stroke heavy duty high performance industrial type diesel engine.

### 6.1 INSULATION SYSTEM

- The insulation system is Class H.
- All windings are impregnated in either triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

### 6.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at  $\pm 0.5\%$ . Nominal adjustment by means of a trim pot incorporated on the AVR.

### 6.3 MOTOR STARTING

An overload capacity equivalent to 300% of the full Load. Impedance at Zero Power Factor can be sustained for 10 seconds, when AREO or PMG option is fitted.

## 7. MOUNTING ARRANGEMENT

### 7.1 BASE FRAME

The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

### 7.2 COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

### 7.3 ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine/Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

### 7.4 SAFETY GUARDS

The fan & fan drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

## 8. FACTORY TESTS

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and its systems are checked before dispatch.

## 9. EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

## 10. DOCUMENTATIONS

Operation & Maintenance manual, circuit wiring diagrams and Commissioning / Fault finding instruction leaflets are accompanied with the Generator.

## 11. QUALITY STANDARDS

The equipment meets the following standards: BS4999, BS5000, BS5514 IEC 60034, VdE0530, NEMA MG 1.22 and ISO 8528.

## 12. WARRANTY

All of the Generating Sets are covered under a warranty policy for a period of 12 months. Warranty of the equipment is in line with manufacturers warranty terms & conditions.

In line with continuous product development, we reserve the right to change specifications without notice.

We offer a range of optional features & accessories to tailor our generating sets to meet you power needs.

## Generating Set Options

### Engine

- Electronic Governor
- Manual Oil Drain Pump
- Coolant Heater and Thermostat
- Exhaust Temperature Monitoring

### Alternator

- Alternator Space Heater
- Auxiliary Winding

### Cooling system

- Remote Radiator Cooling
- Hot and Fresh Air Ducting

### Exhaust Options (open unit)

- Exhaust Silencer – Residential  
(Noise Attenuation 25 -18 dBA)
- Exhaust Silencer – Critical  
(Noise Attenuation 34 -25 dBA)

### Fuel options

- Fuel Water Separator
- Free Standing fuel tank delivered loose
- Bundled Retention Tank
- Manual and/or automatic fuel pump
- Fuel Tank Level Switch
- High Fuel Level Warning
- Low Fuel Level Warning
- Low fuel Level Shutdown

### Electrical System

- Battery Charger 240 V/ 12 V, 10 A
- Analog Metering
- 4 Pole Circuit Breaker
- Battery Isolator Switch
- Automatic Mains Failure Kit
- Manual & Automatic Transfer Switch Panel
- PMG Kit.
- Load Bank

### Enclosed unit

- Weather Proof Enclosure
- Sound Proof Enclosure
- Room Insulation
- Sand filters for tropical climate

### Voltage Connections

- 440 / 254 V
- 416 / 240 V
- 400 / 230 V
- 380 / 220 V
- 220 / 127 V
- 200 / 115 V
- 190 / 110 V

### Genuine spares

For further information on all of the standard and optional features accompanying this product please contact your local dealer or visit [www.Jubaili.com](http://www.Jubaili.com)



Powered by:



ISO 9001

In line with our policy of continuous product development, we reserve the right to change specification without notice.

**Showroom:** Airport Highway, Plaza 1, Bldg. Gr. Floor,  
Tel/Fax: +961 1 840209/ 224/ 228 - Mobile: +961 3 758392  
P.O.Box: 14-5143 Beirut

**24/7 Hotline Maintenance:** +961 71 911455